



DISTRAN[®]
SWITZERLAND

Ultra Pro

Ultrasound Imaging
for Gas Leak Detection



APPLICATIONS

- ▶ Predictive maintenance of high-availability plants
- ▶ Urgent leak searches on assets
- ▶ Inspections prior and after planned maintenance activities
- ▶ Routine checks for toxic or explosive gases
- ▶ Cost-effective maintenance of systems using atmospheric gases (compressed air, nitrogen, argon, etc.)

FEATURES

- ▶ Pinpoint leaks of any gas in real-time
- ▶ Inspect from a safe distance
- ▶ Take pictures and videos of detected leaks
- ▶ Real-time leak rate estimation to set priorities
- ▶ Integrated reporting system

DESCRIPTION

The ultrasound camera Ultra Pro uses 124 integrated microphones to locate ultrasound emitted by leaks of all types of gases and vacuum. The sound source location is indicated in real time on an integrated screen. Pictures and videos can be recorded and integrated in digital reports with Distran Audalytics.

TECHNOLOGY

At the core of Ultra Pro are the multiple sensing elements included in its head. When a sound wave hits the surface of the device, it reaches the elements at times that differ by less than a millisecond. These little time differences are processed by the device in real time to display the location of the sound sources.

distran.swiss

SPECIFICATIONS

Detected gases	All compressed gases incl. air, vacuum and steam
Minimum working distance	30 centimeters (1 ft)
Detection capabilities	0.15 L/h at 0.3 m (0.005 SCFH at 1 ft) 0.2 L/h at 1 m (0.007 SCFH at 3 ft) 9 L/h at 10 m (0.3 SCFH at 32 ft) <i>For a 1.5 bar (22 PSI) gas leak detected in a quiet environment</i>
Acoustic angle of view	180°
Optical angle of view	Fisheye: >150° Wide: 120°
Optical zoom	2X
Weight	1.5 kg (3.3 lb)
Battery life	5 hours (2.5 h x 2 batteries)
Ultra Pro X <i>(Ex-Proof option)</i>	II 3G Ex ic IIC T5 Gc II 3D Ex ic IIIC T100°C Dc Tamb= -10°C to 40°C
Certifications	CE, RoHS and WEEE compliant ATEX and IECEx for Ultra Pro X (Zone 2, including hydrogen)
Operating temperature range	Ultra Pro: -20°C to 50°C (-4°F to 122°F)
Integrated LED lights	1400 lumens
Output format	JPEG and AVI
Data export	Audalytics or SD card
Input methods	Button and touchscreen



DISTRAN[®]
SWITZERLAND

Distran AG

Heinrichstrasse 200
8005 Zurich, Switzerland
sales@distran.ch
+41 44 271 15 79 (CH)

*Specifications subject to change without notice
Modification not permitted without written
consent from Distran AG*
© Distran AG 2025